




CORBREW30W				
  	<b>LED Type</b>	Epistar		
	<b>Color</b>	Warm(2700-3500K)	Nature(4000-4500K)	Cold(5000-6500K)
	<b>Lux a 1 Meter</b>	153+-10	187+-10	222+-10
	<b>Flux□LM□</b>	2045	2225	2375
<b>LM/W</b>	80±10			
<b>CRI</b>	>65			
<b>Power</b>	30W±10%			
<b>Input Voltage</b>	AC85V to AC265V 50/60Hz			
<b>PF</b>	>0.8			
<b>LED Driver</b>	Constant current driver			
<b>Materials</b>	Die-cast aluminum & PMMA lens			
<b>Work Temperature</b>	-30□to+60□			
<b>Environment Humidity</b>	<95%RH			
<b>Lifetime</b>	40,000-50,000 Hours			
				

**Applications:**

- Roadway Lighting, Pathway Lighting, Sidewalk Lighting
- Parking Lot Lighting, Ramp Lighting, Farm Lighting
- Remote Area Lighting, Shopping Mall Lighting
- Warehouse Lighting, Vehicular tunnel Lgihting, etc

**Advantages:**

- No RF interference
- low heat radiation, security , fast response
- low power consumption, high intensity
- long lifetime.



GreenTech

Eco Energy Solutions

